

## HIRING AND USING THE ALLSAW

### REFER TO THE ALLSAW APPLICATION GUIDE

- ALWAYS USE THE RIGHT BLADE FOR THE JOB.
- MAKE SURE THE BLADES FEEL SHARP AND ARE TIGHT.
- USE A CONSTANT ROCKING 'TOE & HEELING' MOTION ESPECIALLY WHEN PLUNGING DEEP.
- LET THE BLADES DO THE WORK.
- GIVE THE BLADES SPACE TO MOVE, SO THEY DO NOT OVERHEAT.
- THE DEEPER YOU PLUNGE, THE MORE ROCKING MOTION IS NEEDED TO GENERATE THE SPACE TO KEEP THE BLADES MOVING FREELY,
- FAILURE TO DO THIS WILL MEAN THE BLADES GET TIGHT, & OVER OVERHEAT. EVENTUALLY THE BRAZING CAN MELT AND RESULT IN TEETH LOSS.
- IF YOU HIT A WALL TIE, BACK OFF AND WORK AROUND IT.

DON'T FORCE THE SAW, TREAT IT WITH RESPECT, UNDERSTAND IT AND HAVE A GREAT SUCCESS.

TAKE A SELECTION OF SPARE BLADES, SO YOU ARE EQUIPPED TO EXPERIMENT AND BENEFIT FROM A WIDER RANGE OF APPLICATIONS.

'IT IS AMAZING WHAT THE ALLSAW CAN DO'

HUNDREDS ARE REAPING THE BENEFITS OF HIRING THE ALLSAW...

...WE WANT YOU TO TOO!

ALLSAW HELPLINE 0800 980 99 99